

# PRODUCT SPECIFICATIONS FOR 1702 MM (67 IN)



<b>Interface Type</b>	IT Coupler
<b>Tine Configuration</b>	Swinging, Floating
<b>Height</b>	74 in
<b>Weight</b>	1450.6 lb
<b>Width</b>	67 in
<b>Length</b>	20.7 in
<b>Tine Spacing Range - Outside Width</b>	909-1487 mm (36-59 in)

# PRODUCT SPECIFICATIONS FOR 1705 MM (67 IN)



<b>Interface Type</b>	Fusion™ Coupler
<b>Tine Configuration</b>	Swinging, Floating
<b>Height</b>	74 in
<b>Weight</b>	1455 lb
<b>Width</b>	67.1 in
<b>Length</b>	20.5 in
<b>Tine Spacing Range - Outside Width</b>	942-1487 mm (37-59 in)

# PRODUCT SPECIFICATIONS FOR 1827 MM (72 IN)



<b>Interface Type</b>	IT Coupler
<b>Tine Configuration</b>	Non-swinging, Floating
<b>Height</b>	59.2 in
<b>Weight</b>	978.9 lb
<b>Width</b>	71.9 in
<b>Length</b>	17.5 in
<b>Tine Spacing Range - Outside Width</b>	1150-1725 mm (45-68 in)

# PRODUCT SPECIFICATIONS FOR 1869 MM (74 IN)



<b>Interface Type</b>	Fusion™ Coupler
<b>Tine Configuration</b>	Non-swinging, Floating
<b>Height</b>	59.8 in
<b>Weight</b>	1166.2 lb
<b>Width</b>	73.6 in
<b>Length</b>	19.1 in
<b>Tine Spacing Range - Outside Width</b>	942-1769 mm (37-70 in)

# PRODUCT SPECIFICATIONS FOR 2134 MM (84 IN)



<b>Interface Type</b>	Fusion™ Coupler
<b>Tine Configuration</b>	Non-swinging/Non-floating
<b>Height</b>	59.3 in
<b>Weight</b>	1911.4 lb
<b>Width</b>	86.5 in
<b>Length</b>	18.5 in
<b>Tine Spacing Range - Outside Width</b>	2041-636 mm (80.4-25 in)

# PRODUCT SPECIFICATIONS FOR 2184 MM (86 IN)



<b>Interface Type</b>	Fusion™ Coupler
<b>Tine Configuration</b>	Non-swinging, Floating
<b>Height</b>	59.8 in
<b>Weight</b>	1241.2 lb
<b>Width</b>	85.6 in
<b>Length</b>	19.1 in
<b>Tine Spacing Range - Outside Width</b>	942-2074 mm (37-82 in)

# PRODUCT SPECIFICATIONS FOR 2196 MM (87 IN)



<b>Interface Type</b>	IT Coupler
<b>Tine Configuration</b>	Floating, Swinging
<b>Height</b>	59.3 in
<b>Weight</b>	1911.4 lb
<b>Width</b>	86.5 in
<b>Length</b>	18.5 in
<b>Tine Spacing Range - Outside Width</b>	848-2094 mm (33-82 in)

# PRODUCT SPECIFICATIONS FOR 2659 MM (105 IN)



<b>Interface Type</b>	Pin On
<b>Tine Configuration</b>	Non-swinging, Non-floating
<b>Height</b>	56.8 in
<b>Weight</b>	1651.3 lb
<b>Width</b>	104.7 in
<b>Length</b>	23.3 in
<b>Tine Spacing Range - Outside Width</b>	1239-2551 mm (49-100 in)



# PRODUCT SPECIFICATIONS FOR 2659 MM (105 IN)



<b>Interface Type</b>	Fusion™ Coupler
<b>Tine Configuration</b>	Non-swinging, Non-floating
<b>Height</b>	57.4 in
<b>Weight</b>	1552.1 lb
<b>Width</b>	104.7 in
<b>Length</b>	18.9 in
<b>Tine Spacing Range - Outside Width</b>	1002-2551 mm (40-100 in)

# PRODUCT SPECIFICATIONS FOR 2812 MM (111 IN)



<b>Interface Type</b>	Pin On
<b>Tine Configuration</b>	Non-swinging, Non-floating
<b>Height</b>	56.8 in
<b>Weight</b>	1761.5 lb
<b>Width</b>	110.7 in
<b>Length</b>	23.3 in
<b>Tine Spacing Range - Outside Width</b>	1391-2703 mm (55-107 in)